

**1** Preparation of subfloor. Topboard and baseboard are shown. Dimensions: 22 3/64", 31 7/64", 56 cm, 79 cm. Thicknesses: 2 mm, 5/64", 4 mm, 5/32", 6 mm, 15/64".

**2** Environment requirements: 24h, 45%-65% humidity, 18°C, and a crossed-out icon for moisture.

**3** Humidity requirements: RH < 75%. \* sand cement screed 2%, \* wooden floor 10%, \* anhydrite 0,5%.

**4** Checking floor level with a 1-meter straightedge. Max. 3 mm deviation, 1/8" tolerance.

**5** Applying Unifloor PE-foil (150 µm, 4 mil) and Unifloor alutape. Dimensions: 1 15/16", 50 mm, 12", 200 mm.

**6** Preparing the base material.

**7** Cutting the base material.

**8** Laying the base material.

**9** Installing the side strip. Dimension: 15/64", 6 mm.

**10** Laying the base material. Dimensions: 31 7/64", 79 cm, 28 cm, 11 1/32", 28 cm.

**11** Cutting the base material. Dimensions: 23 5/16", 59 cm, 31 7/64", 79 cm, 7 51/64", 20 cm, 28 cm, 11 1/32", 28 cm.

**12** Cutting the base material. Dimensions: 23 5/16", 59 cm, 31 7/64", 79 cm, 7 51/64", 20 cm, 56 cm, 22 3/64".

**13** Laying the topboard. Dimensions: 28 x 59, 28 x 79, 56 x 79, 56 x 59, 56 x 79, 56 x 79, 56 x 79. Thicknesses: 31 7/64", 23 5/16", 22 3/64", 11 1/32", 7 51/64", 79 cm, 59 cm, 56 cm, 28 cm, 20 cm.

**14** Laying the topboard. Dimensions: 31 7/64", 79 cm, 15 35/64", 39,5 cm, 39,5 cm, 22 3/64", 56 cm, 56 cm.

**15** Laying the topboard. Dimensions: 31 7/64", 22 3/64", 79 cm, 56 cm. **Follow sequence!**

**16** Sanding the topboard. 120 grain sand paper.

**17** Expansion joints. Max. 10 m, 33', 15/32", min. 12 mm.

**18** Expansion joints between rooms. 15/32", min. 12 mm.

**19** Final preparation. 48h, 6 mm, 15/64".

**Unifloor Underlay Systems**  
Arnsbergstraat 4  
7418 EZ Deventer - The Netherlands  
T +31 (0) 570 85 55 33  
E info@unifloor.nl

**UK Toll Free 0845 603 0 906**

**Service-Line für Deutschland,  
Österreich & Schweiz:**  
T +49 (152) 264 111 11

# Marathon<sup>®</sup> DUAL

- ◆ Fast track floor prep system
- ◆ For Cushion Vinyl and Click LVT
- ◆ Levels out the substrate
- ◆ Creates a super smooth surface
- ◆ Perfectly stable
- ◆ Warmer feel on concrete
- ◆ High impact noise reduction
- ◆ Eco friendly

Marathon<sup>®</sup>  
DUAL

Marathon<sup>®</sup>  
PREMIUM

Marathon<sup>®</sup>  
SUPER

FITTING INSTRUCTION FILM



**uniFloor**  
UNDERLAY SYSTEMS BV

Unifloor Underlay Systems  
Arnsbergstraat 4  
7418 EZ Deventer - The Netherlands  
T +31 (0) 570 85 55 33  
E info@unifloor.nl

UK Toll Free 0845 603 0 906

Service-Line für Deutschland,  
Österreich & Schweiz:  
T +49 (152) 264 111 11

[www.unifloor.nl](http://www.unifloor.nl)